

CONCRETE & MASONRY

Page: 1

Compilation date: 27/04/2015

Revision date: 08/06/2018

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CONCRETE & MASONRY

Product code: 90/00

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name:	Greyland Ltd	
	Unit 9	
	Fifth Avenue	
	Tameside Park Industrial Estate	
	Dukinfield	
	Cheshire	
	SK16 4PP	
Tel:	+44 (0) 161 343 3830	
Fax:	+44 (0) 161 343 0608	
Email:	sales@greyland.co.uk	

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1B: H314; STOT SE 3: H335

Most important adverse effects: Causes severe skin burns and eye damage. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark



Signal words:DangerPrecautionary statements:P260: Do not breathe dust/fumes/gas/mist/vapours/spray.P280: Wear protective gloves/eye protection.

CONCRETE & MASONRY

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomitingP303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.Rinse skin with water .P304+P340: IF INHALED: Remove person to fresh air and keep comfortable forbreathing.P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Removecontact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCHLORIC ACID

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-595-7	-	-	Skin Corr. 1B: H314; STOT SE 3: H335	10-30%
ALCOHOLS, C9-11, ETHOXYLATED				
614-482-0	68439-46-3	-	Eye Dam. 1: H318; Acute Tox. 4: H302	1-10%

Section 4: First aid measures

4.1. Description of first aid measures Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning. Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible. Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible. 4.2. Most important symptoms and effects, both acute and delayed Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate. Eye contact: Corneal burns may occur. May cause permanent damage. **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be

bleeding from the mouth or nose.

Page: 2

CONCRETE & MASONRY

Page: 3

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eves.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

CONCRETE & MASONRY

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HYDROCHLORIC ACID...100%

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	2 mg/m3	8 mg/m3	-	-

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Impermeable gloves.
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection:	Impermeable protective clothing.
Environmental:	Emissions from ventilation or work process equipment should be checked to ensure
	they comply with the requirements of environmental protection legislation. In some
	cases, fume scrubbers, filters or engineering modifications to the process equipment
	will be necessary to reduce emissions to acceptable levels.

Section 9: Physical and chemical properties

9.1. Information on basic physi	9.1. Information on basic physical and chemical properties	
State:	Liquid	
Colour:	Red	
Odour:	Characteristic odour	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Soluble	
Viscosity:	Non-viscous	
Flash point℃:	>70	pH: <2

CONCRETE & MASONRY

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ALCOHOLS, C9-11, ETHOXYLATED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>300 - <2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.

CONCRETE & MASONRY

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

- -		•	•	
Section 12: Ecological informa	tion			
12.1. Toxicity				
Hazardous ingredients:				
ALCOHOLS, C9-11, ETHOXY	LATED			
FISH		96H LC50	1-10	mg/l
	 .		1	
12.2. Persistence and degradal	pility			
Persistence and degradability:	Biodegradable.			
12.3. Bioaccumulative potentia				
Bioaccumulative potential:	No bioaccumulation potenti	ial.		
12.4. Mobility in soil				
<u> </u>	D			
-	Readily absorbed into soil.			
12.5. Results of PBT and vPvB	assessment			
PBT identification:	This product is not identified	d as a PBT/vPvB subst	ance.	
12.6. Other adverse effects				
Other adverse effects:	Negligible ecotoxicity.			
Section 13: Disposal consideration	ations			
-				
13.1. Waste treatment methods	5			
Disposal operations:	Transfer to a suitable conta	ainer and arrange for co	llection by specialised	disposal
	company.			
NB:	The user's attention is draw	n to the possible existe	ence of regional or nat	ional
	regulations regarding dispo	osal.		
Section 14: Transport information	ion			
14.1. UN number				
UN number:	UN1789			
14.2. UN proper shipping name	•			
Shipping name:	HYDROCHLORIC ACID			
14.3. Transport hazard class(es	5)			
Transport class:	8			
-	-			
14.4. Packing group				

r acking group

Packing group: ||

CONCRETE & MASONRY

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information:	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation
	(EU) 2015/830
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H318: Causes serious eye damage.
	H335: May cause respiratory irritation.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.