

# FLOORCARE

1706/01  
5 LITRE

## CRYLCEEL INFORMATION SHEET

### USE:

A water emulsion floor sealer based on an exceptionally tough thermoplastic acrylic polymer. Provides the perfect foundation for metallised polishes, it is particularly good for old linoleum and other impoverished floors that have become porous. Also suitable for interior stone and concrete and will prevent concrete floors from dusting.

### DIRECTIONS:

All these polishes have a drying time of between 25-35 minutes depending on conditions. The coverage will vary between 50 to 60m per litre depending upon the solids content and the porosity of the floor. The floor should be thoroughly cleaned to remove all traces of old polishes and sealers. The sealer is made to last and any dirt left on the floor will remain until the sealer is removed. Application should be with a standard mop, DO NOT USE applicators which will generate excessive foam. Apply to the floor sparingly in a thin even film. Use long even strokes, do not rub. Two coats of sealer should be applied. Allow the first coat to dry thoroughly and evenly before applying the second coat. Do not over apply. This will provide a perfect base for a quality finish when applied on hard surface flooring. Always clean applicators with clean water after use.

### TECHNICAL:

State:	Liquid
Colour:	Off-white
Odour:	Characteristic odour
Solubility in water:	Soluble
Viscosity:	Non-viscous
Boiling point/range°C:	100
Flash point°C:	>70
pH Level:	7-8

**PERSISTENCE AND DEGRADABILITY:** Biodegradable.

## CRYLCEEL ACRYLIC FLOOR SEALER

A water emulsion floor sealer based on an exceptionally tough thermoplastic acrylic polymer. Provides the perfect foundation for metallised polishes, it is particularly good for old linoleum and other impoverished floors that have become porous. Also suitable for interior stone and concrete and will prevent concrete floors from dusting.

### DIRECTIONS

All these polishes have a drying time of between 25-35 minutes depending on conditions. The coverage will vary between 50 to 60m per litre depending upon the solids content and the porosity of the floor. The floor should be thoroughly cleaned to remove all traces of old polishes and sealers. The sealer is made to last and any dirt left on the floor will remain until the sealer is removed. Application should be with a standard mop, DO NOT USE applicators which will generate excessive foam. Apply to the floor sparingly in a thin even film. Use long even strokes, do not rub. Two coats of sealer should be applied. Allow the first coat to dry thoroughly and evenly before applying the second coat. Do not over apply. This will provide a perfect base for a quality finish when applied on hard surface flooring. Always clean applicators with clean water after use.

**KEEP FROM FREEZING**  
Keep locked up and out of reach of children. In case of contact with eyes, wash immediately with plenty of water and seek medical advice. Do not mix with other chemicals.  
CONTAINS: 2-(2-Butoxyethoxy) Ethanol - less than 10%, Ethylene Glycol - less than 10%, Trimethoxethyl Phosphate - less than 10%



**5L**

**GREYLAND**

Greyland Ltd • Tameside Park Ind Est • SK16 4PP  
Tel: 0161 343 3830 • www.greyland.co.uk

Code: 1706/01



Greyland Ltd • Tameside Park Ind Est • SK16 4PP  
Tel: 0161 343 3830 • www.greyland.co.uk